



US010107578B1

(12) **United States Patent**
Mirabel

(10) **Patent No.:** **US 10,107,578 B1**
(45) **Date of Patent:** **Oct. 23, 2018**

- (54) **CASING CATCHER FOR AR-STYLE RIFLE**
- (71) Applicant: **Michael R. Mirabel**, Folsom, CA (US)
- (72) Inventor: **Michael R. Mirabel**, Folsom, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: **15/697,682**
- (22) Filed: **Sep. 7, 2017**
- (51) **Int. Cl.**
F41A 9/60 (2006.01)
- (52) **U.S. Cl.**
CPC **F41A 9/60** (2013.01)
- (58) **Field of Classification Search**
CPC F41A 9/60; F41A 9/81
USPC 42/98
See application file for complete search history.

4,903,426	A *	2/1990	Bammate	F41A 9/60	42/98
5,398,439	A *	3/1995	Harless	F41A 9/60	42/98
5,651,208	A *	7/1997	Benson	F41A 9/60	42/106
7,043,863	B2 *	5/2006	Saur	F41A 9/60	206/3
7,536,821	B1 *	5/2009	Saur	F41A 9/60	181/252
2005/0188599	A1 *	9/2005	Saur	F41A 9/60	42/98
2006/0248776	A1 *	11/2006	Saur	F41A 9/60	42/98

* cited by examiner

Primary Examiner — Samir Abdosh

(74) Attorney, Agent, or Firm — Craig A. Simmermon

(57) **ABSTRACT**


Casing catcher for AR-style rifle is an ammunition cartridge casing catcher, shell casing catcher, or brass catcher that is reversibly attachable to any AR-style rifle. Casing catcher for AR-style rifle uses a reversibly attachable means to magnetically reversibly attach to the inside surface of the ejection port cover on any AR-style rifle with a two key picatinny rail attachment system to reversibly align itself properly and attach itself to the AR-style rifle. Casing catcher for AR-style rifle has a cage, a magnetic weir plate, a lock pin receiver, a lock pin, a first key, and a second key. Magnetic weir plate has at least one magnet attached thereto. The first key to has a special shape or profile that includes a special right facing foot protuberance that is the inverse shape of the left side of the picatinny rail on any AR-style rifle. The second key has a special shape or profile that includes a special left facing foot protuberance that is the inverse shape of the right side of the picatinny rail on any AR-style rifle.



1 Claim, 7 Drawing Sheets

(56) **References Cited**

U.S. PATENT DOCUMENTS

577,452	A *	2/1897	Richardson	A47L 13/52	15/257.2
663,262	A *	12/1900	Dieterich	F41A 9/60	224/0.5
1,201,189	A *	10/1916	Johnson	F41A 9/60	224/0.5
2,354,277	A *	7/1944	Richardson	F41A 9/60	42/98
3,153,981	A *	10/1964	Brass	F41A 9/60	42/98
3,658,241	A *	4/1972	Pistocchi	F41A 9/60	232/1 R
3,739,685	A *	6/1973	Lundgren	F41A 9/60	42/98
4,166,333	A *	9/1979	Kratzer	F41A 9/60	42/98








FIG. 3




FIG. 4




FIG. 5

FIG. 6








FIG. 7







CASING CATCHER FOR AR-STYLE RIFLE

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention pertains to an ammunition cartridge casing catcher, shell casing catcher, or brass catcher that is reversibly attachable to any AR-style rifle. When the invention is attached to an AR-style rifle, the invention functions to catch, save, and accumulate all spent ammunition casings that are ejected from the rifle where the rifle ejects one such spent ammunition casing each time the rifle is fired.

2. Description of Related Art

The AR-Style rifle was first developed in the 1950's by Eugene Stoner and the ArmaLite Company, which was a division of Fairchild Engine and Aircraft Corporation at that time. The AR stands for ArmaLite. ArmaLite developed many rifles with the designation of AR including: AR-5, AR-10, and AR-15. The AR-15 rifle design is the most widely used of the different AR-Style designs. An ejection port cover is a feature on all AR-Style rifles. A picatinny rail is a feature on most AR-Style rifles. A picatinny rail is also known as a pic rail, a MIL-STD-1913 rail, or a standardization agreement 2324 rail. This invention reversibly attaches to the ejection port cover and picatinny rail of any AR-Style rifle.

There are many ammunition cartridge casing catchers, shell casing catchers, or brass catchers in the prior art that are reversibly attachable to an AR-Style rifle. However, none include a reversibly attachable means to magnetically reversibly attach to the inside surface of the ejection port cover on any AR-style rifle combined with a two key picatinny rail attachment system to reversibly align itself properly and attach itself to the AR-style rifle. The magnetic reversible attachment means with two key picatinny rail attachment system is further described below.

BRIEF SUMMARY OF THE INVENTION

It is an aspect of casing catcher for AR-style rifle to catch, save, and accumulate all spent ammunition casings that are ejected from the rifle where the rifle ejects one such spent ammunition casing each time the rifle is fired.

It is an aspect of casing catcher for AR-style rifle to include a cage to catch, save, and accumulate therein all spent ammunition casings that are ejected from the rifle.

It is an aspect of casing catcher for AR-style rifle to utilize a reversibly attachment means to reversibly itself to any AR-style rifle.

It is an aspect of reversibly attachment means to magnetically attach to the inside surface of an open ejection port cover on any AR-style rifle.

It is an aspect of reversibly attachment means to utilize one or more magnets to reversibly attach itself to the inside surface of an open ejection port cover on any AR-style rifle.

It is an aspect of reversibly attachment means to utilize a locating notch to align itself over the protrusion from the detent on the inside surface of an open ejection port cover on any AR-style rifle.

It is an aspect of casing catcher for AR-style rifle to utilize a two key picatinny rail attachment system to reversibly align itself and reversibly attach itself to the picatinny rail on any AR-style rifle.

It is an aspect of two key picatinny rail attachment system to locate and reversibly attach both keys within one slot or groove in the picatinny rail on any AR-style rifle.

It is an aspect of each key to have a special shape or profile that forms a slip fit or press fit within one slot or groove in the picatinny rail on any AR-style rifle.

It is an aspect of one key to have a special shape or profile that includes a special right facing foot protuberance that is the inverse shape of the left side of the picatinny rail on any AR-style rifle.

It is an aspect of the other key to have a special shape or profile that includes a special left facing foot protuberance that is the inverse shape of the right side of the picatinny rail on any AR-style rifle.

It is an aspect of the two key picatinny rail alignment system to utilize a lock pin to reversibly attach and lock both keys to casing catcher for AR-style rifle.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a right front perspective view of casing catcher for AR-style rifle.

FIG. 2 is a front left perspective view of casing catcher for AR-style rifle.

FIG. 3 is a perspective view of casing catcher for AR-style rifle properly attached to an AR-style rifle.

FIG. 4 is an exploded perspective view of casing catcher for AR-style rifle and AR-style rifle.

FIG. 5 is a partially exploded front elevation view of casing catcher for AR-style rifle and AR-style rifle.

FIG. 6 is a front elevation view of casing catcher for AR-style rifle.

FIG. 7 is a left side elevation view of casing catcher for AR-style rifle.

FIG. 8 is a rear elevation view of casing catcher for AR-style rifle.

FIG. 9 is a right side elevation view of casing catcher for AR-style rifle.

FIG. 10 is a perspective view of magnetic weir plate.

DEFINITION LIST

Term	Definition
5	Casing Catcher for AR-Style Rifle
10	Cage
12	Cage Upper Side
13	Cage Lower Side
14	Cage Front Side
15	Cage Rear Side
16	Cage Left Side
17	Cage Right Side
18	Left Diagonal Side
19	Right Diagonal Side
20	Magnetic Weir Plate
22	Magnet
24	Alignment Notch
26	Ejection Port Cover Hinge Tab
28	Ambidextrous Bolt Catch Clearance Notch
30	Lock Pin Receiver
32	Lock Pin Bore
34	Key Slot
40	Lock Pin
42	Lock Pin Ring
50	First Key
52	First Key Lock Pin Hole
54	First Key Shaft
56	Right Facing Foot Protuberance
60	Second Key
62	Second Key Lock Pin Hole
64	Second Key Shaft

-continued

DEFINITION LIST	
Term	Definition
66	Left Facing Foot Protuberance
100	AR-Style Rifle
101	Ejection Port
102	Ejection Port Cover
103	Ejection Port Cover Detent
104	Rear Protusion on Ejection Port Cover Hinge
105	Picatinny Rail
106	Ridge in Picatinny Rail
107	Groove in Picatinny Rail

DETAILED DESCRIPTION OF THE INVENTION

Casing catcher for AR-style rifle 5 comprises: a cage 10; a magnetic weir plate 20; a lock pin receiver 30; a lock pin 40; a first key 50; and a second key 60.

Cage 10 comprises: an upper side 12, a lower side 13, a front side 14, a rear side 15, a left side 16, and a right side 17. Cage 10 is an enclosed container or cage that functions to catch, save, and accumulate all spent ammunition casings that are ejected from the AR-style rifle 100. Upper side 12 is a rigid horizontal rigid planar member with an upper surface, a lower surface, a front edge, a right edge, a rear edge, and a left edge. Lower side 13 is a rigid horizontal planar member with an upper surface, a lower surface, a front edge, a right edge, a rear edge, and a left edge. Front side 14 is a rigid vertical planar member with a front surface, a rear surface, an upper edge, a right edge, a lower edge, and a left edge. Rear side 15 is a rigid vertical planar member with a front surface, a rear surface, an upper edge, a right edge, a lower edge, and a left edge. Left side 16 is a rigid vertical planar member with a left surface, a right surface, a front edge, an upper edge, a rear edge, and a lower edge. Right side 17 is a rigid vertical planar member with a left surface, a right surface, a front edge, an upper edge, a rear edge, and a lower edge. Rigid planar members may be continuous and without holes, apertures, or slots. Alternately, rigid planar members may have holes, apertures, or slots. Best mode planar members include holes, apertures, or slots, which function to allow for faster dissipation of heat from the spent ammunition casings, which are very hot after ejection from the AR-style rifle 100. Rigid planar members are depicted with heat dissipation slots. Holes, apertures, or slots may not have an overall dimension or width that is greater than that of the spent ammunition casings in order to prevent the spent ammunition casing from falling through the holes, apertures, or slots.

The front edge of upper side 12 is rigidly attached to the upper edge of front side 14. The right edge of upper side 12 is rigidly attached to or is immediately adjacent to the upper edge of right side 17. The rear edge of upper side 12 is rigidly attached to the upper edge of rear side 15. The front edge of lower side 13 is rigidly attached to the lower edge of front side 14. The right edge of lower side 13 is rigidly attached to or is immediately adjacent to the lower edge of right side 15. The rear edge of lower side 13 is rigidly attached to the lower edge of rear side 15. The left edge of lower side 13 is rigidly attached to or is immediately adjacent to lower edge of left side 14. The front edge of left side 16 is rigidly attached to left edge of front side 14. The rear edge of left side 16 is rigidly attached to the left edge of rear side 15. The front edge of right side 17 is rigidly

attached to right edge of front side 14. The rear edge of right side 17 is rigidly attached to the right edge of rear side 15.

Rigid attachment between edges of sides 12,13,14,15,16, 17 functions to retain spent ammunition casings between sides 12,13,14,15,16,17 and to prevent spent ammunition casings from falling out of cage 10. Rigid attachment may be accomplished by any known means such as by fasteners, screws, bolts, mortise and tenon joint, dovetail joint, tongue and groove joint, any known type of joint, sonic welding, welding, glue, adhesive, or epoxy. Likewise, the immediate adjacent placement of edges of sides is used to retain spent ammunition casings between sides 12,13,14,15,16,17 and to prevent spent ammunition casings from falling out of cage 10. The seam or gap between edges positioned immediately adjacent to each other must be less than the overall width of the spent ammunition casings or less than about one third of an inch.

The upper edge of left side 16 is not attached to or adjacent to the left edge of upper side 12 in order to provide a gap or hole between upper edge of left side 16 and the left edge of upper side 12. This gap provides clearance space for spent ammunition casings to enter or fall into cage 10 after being ejected from the AR-style rifle 100. Magnetic weir plate 20 is installed within this gap as described below.

Alternately, there may be a left diagonal side 18 in order to provide for a larger cage volume. Left diagonal side 18 is a rigid diagonal planar member with a left surface, a right surface, a front edge, an upper edge, a rear edge, and a lower edge. In this mode, the lower edge of left diagonal side 18 is rigidly attached to or is immediately adjacent to the upper edge of left side 16. The front edge of left diagonal side 18 is rigidly attached to left edge of front side 14. The rear edge of left diagonal side 18 is rigidly attached to the left edge of rear side 15.

Alternately, there may be a right diagonal side 19 in order to provide for a larger cage volume. Right diagonal side 19 is a rigid diagonal planar member with a left surface, a right surface, a front edge, an upper edge, a rear edge, and a lower edge. In this mode, the lower edge of right diagonal side 19 is rigidly attached to or is immediately adjacent to the upper edge of right side 17. The front edge of right diagonal side 19 is rigidly attached to right edge of front side 14. The rear edge of right diagonal side 19 is rigidly attached to the right edge of rear side 15. Left diagonal side 18 and right diagonal side 19 are roughly parallel to each other. Best mode includes left diagonal side 18 and right diagonal side 19 as depicted.

Rigid attachment between edges of sides is used to retain spent ammunition casings between sides 12,13,14,15,16,17, 18,19 and to prevent spent ammunition casings from falling out of cage 10. Rigid attachment may be accomplished by any known means such as by fasteners, screws, bolts, mortise and tenon joint, dovetail joint, tongue and groove joint, any known type of joint, sonic welding, welding, glue, adhesive, or epoxy. Likewise, the immediate adjacent placement of edges of sides is used to retain spent ammunition casings between sides 12,13,14,15,16,17,18,19 and to prevent spent ammunition casings from falling out of cage 10. The seam between edges positioned immediately adjacent to each other must be less than the overall width of the spent ammunition casings or less than about one third of an inch.

The upper edge of left diagonal side 18 is not attached to or adjacent to the left edge of upper side 12 in order to provide a gap between upper edge of left diagonal side 18 and the left edge of upper side 12. This gap provides clearance space for spent ammunition casings to enter or fall

5

into the cage 10 after being ejected from the AR-style rifle 100. Magnetic weir plate 20 is installed within this gap as described below.

Magnetic weir plate 20 is a rigid diagonal planar member with an upper surface, a lower surface, a front edge, a right edge, a rear edge, and a left edge. Magnetic weir plate 20 is position diagonally with its right edge located above its left edge where the left edge of magnetic weir plate 20 is directed downwards and the right edge of magnetic weir plate 20 is directed upwards as depicted. The right edge of magnetic weir plate 20 is located within the interior of cage 10. The left edge of magnetic weir plate 20 is located just outside of the interior of cage 10. The front edge of magnetic weir plate 20 is rigidly attached to the rear surface of front side 14. The rear edge of magnetic weir plate 20 is rigidly attached to the front surface of rear side 15. Rigid attachment is such as to prevent spent ammunition casing from falling through between the attached members. Magnetic weir plate 20 is positioned so that a spent ammunition casing must travel uphill so to speak along the upper surface of magnetic weir plate 20 in order to fall into cage 10. This does not pose a hindrance to the spent ammunition casing travelling into the cage 10 as every spent ammunition casing is ejected with some velocity perpendicularly outwards from the AR-style rifle 100 after being fired.

The main purpose of the diagonal positioning of the magnetic weir plate 20 is to force all bouncing spent casings back into the cage 10 when they bounce upwards. Sometimes, spent casings already accumulated in the bottom of cage 10 may bounce upwards as a result of a new spent casing being ejected forcefully down onto them. Other times, the new spent casing being ejected bounce upwards as a result being ejected forcefully down onto spent casings already accumulated in the bottom of cage 10. Either way, the diagonal positioning of the magnetic weir plate 20 prevents the casings from bouncing back out of cage 10.

The left edge of magnetic weir plate 20 further comprises at least one magnet 22. At least one magnet 22 is rigidly attached to the left edge of magnetic weir plate 20. Magnet 22 is a magnet. Any known type of magnet may be used. At least one magnet 22 functions to reversibly attach or magnetically attach casing catcher for AR-style rifle 5 onto the inside surface of an open ejection port cover 102 on any AR-Style rifle 100.

Every AR-style rifle 100 has an ejection port 101 and an ejection port cover 102 located on the right side of the rifle 100. Ejection port 101 and ejection port cover 102 are each standard components of any AR-style rifle 100. Ejection port 101 is a void, gap, or hole the upper receiver of AR-style rifle 100 on the right side. Ejection port 101 functions to allow spent ammunition casings to exit the chamber and pass through the ejection port 101 in order to exit the rifle 100. Ejection port cover 102 covers ejection port 101. Ejection port cover 102 is a rigid planar member with an inside surface, an outside surface, an upper end, a lower end, a left end, and a right end. Ejection port cover 102 functions to cover ejection port 101 and protect the firing chamber and bolt of the rifle 100 from the outside elements such as dirt, dust, water, rain, snow, etc. Ejection port cover 102 hinges, rotates, or pivots downward to open and hinges, rotates, or pivots back upward to close. A hinge for this pivotal attachment is located at the lower end of ejection port cover 102. Ejection port cover 102 reversibly pivots around its lower end as depicted. Ejection port cover 102 may be closed by simply pressing it upwards until an ejection port cover detent 103 snaps onto the top of ejection port 101 to automatically snap and lock the ejection port cover 102

6

closed. Ejection port cover 102 automatically opens when a round is fired, when the bolt is pulled back, or when the bolt is released forward. Ejection port cover 102 must be open in order to properly attach casing catcher for AR-style rifle 5 onto AR-style rifle 100. The inside surface of ejection port cover 102 faces the firing chamber and bolt of the rifle 100 or to the left when ejection port cover 102 is closed. The outside surface of ejection port cover 102 faces to the right when ejection port cover 102 is closed.

Magnet 22 has an upper surface and a lower surface. The upper surface of magnet 22 is rigidly attached to the left edge of magnetic weir plate 20. Any known type of rigid attachment may be used including any known type of fastener, rivet, welding, glue, adhesive, or epoxy. In best mode, a fastener, namely a screw is used to attach magnet 22 to the left edge of magnetic weir plate 20, as depicted. The lower surface of magnet 22 is reversibly attachable or magnetically attachable to the inside surface of open ejection port cover 102. The lower surface of magnet 22 is a rigid planar surface that is parallel with the left edge of magnetic weir plate 20, which is also a rigid planar surface. The left edge of magnetic weir plate 20 is sized, shaped, and located so that it is parallel with the inside surface of open ejection port cover 102 as depicted. This parallel alignment between the inside surface of open ejection port cover 102 and the left edge of magnetic weir plate 20 is critical to proper reversibly attachment or magnetic attachment casing catcher for AR-style rifle 5 to AR-style rifle 100. Casing catcher for AR-style rifle 5 may alternately comprise more than one magnet 22, however, it is entirely possible to achieve the required reversible magnetic attachment with only one magnet 22. In best mode, there are four magnets 22 rigidly attached to the left edge of magnetic weir plate 20, as depicted.

The left edge of magnetic weir plate 20 further comprises an alignment notch 24. Alignment notch 24 is a slot, notch, cavity, or keyhole in the middle of left edge of magnetic weir plate 20. Alignment notch 24 is oblong shaped with a vertical longitudinal axis, an upper end, and a lower end. The lower end of alignment notch 24 breaks through the lower surface of magnetic weir plate 20 as depicted. The upper end of alignment notch 24 does not break through the upper surface of magnetic weir plate 20 as depicted. Alignment notch 24 is sized and shaped to make a slip fit with the protrusion from an ejection port cover detent 103 located on the inside surface of ejection port cover 102. Every AR-style rifle 100 has an ejection port cover detent 103 rigidly attached to the inside surface the ejection port cover 102. Ejection port cover detent 103 functions to lock and hold the ejection port cover 102 closed as stated above. The shape of the protrusion from ejection port cover detent 103 the inside surface the ejection port cover 102 is the same on all AR-style rifles. The shape of the ejection port cover detent 103 on the inside surface the ejection port cover 102 is the same on all AR-style rifles. Alignment notch 24 functions to help guide and locate casing catcher for AR-style rifle 5 properly onto the inside surface of open ejection port cover 102 to allow at least one magnet 22 to reversibly attach or magnetically attach properly to the inside surface of open ejection port cover 102. The operator places the protrusion from ejection port cover detent 103 into the alignment notch 24 as at least one magnet 22 comes into contact with the inside surface of ejection port cover 102 to magnetically attach thereto. This method of alignment and attachment is very effective at properly locating and attaching casing catcher for AR-style rifle 5 to an AR-style rifle 100.

The left edge of magnetic weir plate **20** further comprises an ejection port cover hinge tab **26**. Ejection port cover hinge tab **26** is a rigid mass or solid portion of the left edge of magnetic weir plate **20** that contacts the ejection port cover hinge rear protrusion **104**. Ejection port cover hinge tab **26** may be of any particular shape. In best mode, ejection port cover hinge tab **26** is a rectangular cuboid as depicted. Every ejection port cover **102** is pivotally attached to the upper receiver by an ejection port cover hinge. The ejection port cover hinge includes two protrusions on the right surface of the upper receiver just beneath the ejection port cover **102**. There is a front protrusion and a rear protrusion **104**. The ejection port cover hinge tab **26** functions to rest against the rear protrusion **104** of the ejection port cover hinge when the casing catcher for AR-style rifle **5** is properly attached to AR-style rifle **100**. The resting of ejection port cover hinge tab **26** against ejection port cover hinge rear protrusion **104** adds stability to the reversible attachment of casing catcher for AR-style rifle **5**. The resting of ejection port cover hinge tab **26** against ejection port cover hinge rear protrusion **104** prevents lateral movement or vibrations from left to right as the rifle **100** is firing.

Magnetic weir plate **20** may further comprises an ambidextrous bolt catch clearance notch **28**. Ambidextrous bolt catch clearance notch **28** is a void, slot, or cavity located where the rear left corner of magnetic weir plate **20** would be otherwise. Void, slot, or cavity is such that the upper and lower rear left corners of magnetic weir plate **20** are removed and voided as depicted. Thus, the rear left corner of a magnetic weir plate **20** with an ambidextrous bolt catch clearance notch **28** is the rear left corner of ejection port cover hinge tab **26** because of the void to the rear thereof that is the ambidextrous bolt catch clearance notch **28**. Ambidextrous bolt catch clearance notch **28** functions to provide clearance space for an ambidextrous bolt catch. A few types AR-style rifles **100** are ambidextrous. An ambidextrous AR-style rifle **100** has features that are operable from both the left side and the right side of the rifle **100**. Ambidextrous features have control on both sides. A true ambidextrous AR-style rifle **100** has a bolt catch on the right side as well as a bolt catch at the normal location on the left side of the rifle **100**. An ambidextrous bolt catch clearance notch **28** is required for proper attachment and operation of casing catcher for AR-style rifle **5** onto an ambidextrous AR-style rifle **100** with a bolt catch on the right side.

Lock pin receiver **30** is a rigid horizontal support member. Lock pin receiver **30** is made of strong material such as steel, aluminum, hard plastic, composite, carbon fiber, fiberglass, or any other known material with high strength. Lock pin receiver **30** is oblong shaped. Lock pin receiver **30** receiver may have any particular oblong shape such as cylindrical, rectangular cuboid, square cuboid, triangular cuboid, or any other oblong shape. Lock pin receiver **30** has a longitudinal axis, an upper surface, a lower surface, a front end, and a rear end. The longitudinal axis of lock pin receiver **30** is horizontal and parallel with the upper side **12** of cage **10**. The longitudinal axis of lock pin receiver **30** is also parallel with the left edge of the upper side **12** of cage **10**. Lock pin receiver **30** has a lock pin bore **32** running along its longitudinal axis. Lock pin bore **32** is a cylindrical void or cavity running completely along the longitudinal axis of lock pin receiver **30** from the front end of lock pin receiver **30** to the rear end of lock pin receiver **30**. The inner diameter of lock pin bore **32** is sized to make a slip fit with the outer diameter of a lock pin **40**. The lower surface of lock pin receiver **30** is rigidly attached to the upper surface of the upper side **12** of cage **10**. The upper surface of lock pin

receiver **30** has at least one key slot **34**. At least one key slot **34** is a slot shaped void with a longitudinal axis that runs perpendicular to the longitudinal axis of lock pin receiver **30**. At least one key slot **34** has a width that is sized to make a slip fit with the assembly of first key **50** and second key **60** stacked together. Thus, the width of at least one key slot is the thickness of first key **50** plus the width of second **60** plus the required clearance space for the slip fit. More than one key slot **34** may be used. In best mode, there are three key slots **34** in lock pin receiver **30** as depicted. Lock pin receiver functions to help rigidly attach cage **10** to a lock pin **40**.

Lock pin **40** is a rigid horizontal cylindrical member with a longitudinal axis, a first end, and a second end. Lock pin **40** is a lock pin. The second end of lock pin **40** has a lock pin ring attached thereto. Lock pin **40** functions to help rigidly attach first and second keys **50,60** to lock pin **40**. Lock pin **40** is reversibly attachable to lock pin receiver **30** by inserting lock pin **40** through lock pin bore **32** and removing lock pin **40** from the lock pin bore **32** by pulling lock pin **40** out of lock pin bore **32** as depicted.

Picatinny rail **105** is a standard feature on an AR-style rifle **100**. The shape of picatinny rail **105** is standard and well known in the industry. Picatinny rail **105** is a rigid horizontal oblong rigid member with a longitudinal axis. Picatinny rail **105** has a plurality of ridges **106**. Each ridge **106** is specially shaped oblong ridge or protrusion running perpendicular to the longitudinal axis of picatinny rail **105**. Each ridge **106** is identical to all other ridges **106**. Each ridge **106** has a tapered left side that faces upwards and towards the left. Each ridge **106** has a tapered right side that faces upwards and towards the right. Picatinny rail **105** has a plurality of grooves **107**. Each groove **107** is a specially shaped oblong groove, slot, seam, or trough running perpendicular to the longitudinal axis of picatinny rail **105**. Each groove **107** is identical to all other grooves **107**. Each groove **107** has a tapered left side that faces downwards and to the left. Each groove **107** has a tapered right side that faces downwards and to the right.

First key **50** is a key. First key **50** is an oblong rigid planar member with a left end and a right end. First key **50** has a special shape that is defined by a lock pin hole **52**, a key shaft **54**, and a right facing foot protuberance **56**. Lock pin hole **52** is located on the right end of first key **50**. Lock pin hole **52** is a circular shaped void in the rigid planar on the upper side of the right end of oblong rigid planar member as depicted. The inside diameter of lock pin hole **52** is sized to make a slip fit with the outer diameter of a lock pin **40**. Right facing foot protuberance **56** is a rigid foot shaped protuberance extending down from the left end of oblong rigid planar member as depicted. The rigid foot shaped protuberance faces towards the right end of the oblong rigid planar member. Right facing foot protuberance **56** functions to make a slip fit with the tapered left side of picatinny rail **105**. The shape of the left side of picatinny rail **105** is standard and well known in the industry. Right facing foot protuberance **56** is sized and shaped to be the exact inverse shape of the tapered left side of picatinny rail **105**. This inverse shape is a specific shape that looks like the profile of a human foot facing towards the right end of first key **50** as depicted. The foot shape wedges under the tapered left side of picatinny rail **105** to hold first key **50** in place. The top of the foot shape is tapered and shaped like the inverse of the tapered left side of picatinny rail **105**. Key shaft **54** is an oblong rigid planar member with lock pin hole **52** at one end and right facing foot protuberance **56** at the other end as depicted. Lock pin **40** is removeably attachable within lock pin hole **52**.

Second key **60** is a key. Second key **60** is an oblong rigid planar member with a left end and a right end. Second key **60** has a special shape that is defined by a lock pin hole **62**, a key shaft **64**, and a left facing foot protuberance **66**. Lock pin hole **62** is located on the right end of second key **60**. Lock pin hole **62** is a circular shaped void in the rigid planar on the upper side of the right end of oblong rigid planar member as depicted. The inside diameter of lock pin hole **62** is sized to make a slip fit with the outer diameter of a lock pin **40**. Left facing foot protuberance **66** is a rigid foot shaped protuberance extending down from the middle of oblong rigid planar member as depicted. The rigid foot shaped protuberance faces towards the left end of the oblong rigid planar member. Left facing foot protuberance **66** functions to make a slip fit with the tapered right side of picatinny rail **105**. The shape of the right side of picatinny rail **105** is standard and well known in the industry. Left facing foot protuberance **66** is sized and shaped to be the exact inverse shape of the tapered right side of picatinny rail **105**. This inverse shape is a specific shape that looks like the profile of a human foot facing towards the left end of second key **60** as depicted. The foot shape wedges under the tapered right side of picatinny rail **105** to hold second key **60** in place. The top of the foot shape is tapered and shaped like the inverse of the tapered right side of picatinny rail **105**. Key shaft **64** is an oblong rigid planar member with lock pin hole **62** at one end and left facing foot protuberance **66** at its mid section as depicted.

Lock pin **40** is removeably attachable within lock pin hole **62**. The left end of second key **60** is part of the key shaft **64** as depicted. The key shaft **64** continues further to the left end of second key **60** and beyond left facing foot protuberance **66**.

Casing catcher for AR-style rifle **5** is installed onto an AR-style rifle as follows. The ejection port cover **102** must be open. The left edge of magnetic weir plate is positioned adjacent to the inside surface of the open ejection port cover **102**. The alignment notch **24** on magnetic weir plate is aligned with or placed concentrically with the protrusion from ejection port cover detent **103** on inside surface of the open ejection port cover **102**. Then, at least one magnet **22** on the left edge of magnetic weir plate **20** is pressed against the inside surface of the open ejection port cover **102**. With multi magnet **22** modes, all magnets are pressed against the inside surface of the open ejection port cover **102**.

Then the operator must find and choose a particular groove **107** out of the plurality of grooves **107** on picatinny rail **105** that is aligned with at least one key slot **34** on lock pin receiver **30**, which is designated the alignment groove **107**. If using a mode of casing catcher for AR-style rifle **5** with two key slots **34**, there would be two aligned grooves **107** to choose from, one groove that aligns with each key slot **34**. If using a mode of casing catcher for AR-style rifle **5** with three key slots **34**, as depicted, there would be three aligned grooves **107** to choose from, one groove that aligns with each key slot **34**. The operator would then chooses one of these aligned grooves **107** in order to continue with the installation. The advantage of having more than one key slot is that this provides alternative alignment grooves **107** for attachment of the casing catcher for AR-style rifle **5** where some alignment grooves **107** on picatinny rail **105** may not be vacant or available because they could already be in use with the attachment of another device to the picatinny rail **105** such as a rifle scope or other device.

After choosing the particular alignment groove **107**, the first key **50** is positioned into the alignment groove **107** on picatinny rail **105** by placing first key shaft **54** into the

alignment groove **107** with right facing foot protuberance **56** adjacent to and contiguous with the tapered left side of picatinny rail **105** as depicted. The right facing foot protuberance **56** slides under the tapered left side of the alignment groove **107** to wedge or catch itself there, which prevents it from moving upwards. While doing this, the lock pin hole **52** on first key **50** must be positioned concentrically with the lock pin bore **32**. Then, second key **60** is positioned into the same alignment groove **107** on picatinny rail **105** by placing second key shaft **64** into the alignment groove **107** with left facing foot protuberance **66** adjacent to and contiguous with the right side of picatinny rail **105** as depicted. The left facing foot protuberance **66** slides under the tapered right side of the alignment groove **107** to wedge or catch itself there, which prevents it from moving upwards. While doing this, the lock pin hole **62** on second key **60** must be positioned concentrically with the lock pin bore **32**. First key **50** may be placed into in alignment groove **107** before or after second key **60** is placed into alignment groove **107**. First key **50** may be position in front or behind second key **60** when placed into alignment groove **107**.

Finally, the first end of lock pin **40** is inserted completely through the lock pin bore **32**. The first end of lock pin **40** may be started from the front end of lock pin bore **32** or from the rear end of lock pin bore **32**. The placement of lock pin **40** through lock pin bore **32** functions to lock casing catcher for AR-style rifle **5** firmly onto the AR-style rifle **100**.

Casing catcher for AR-style rifle **5** must be detached from the rifle **100** in order to empty the accumulated spent casings or cartridges from cage **10**. The cage **10** is emptied by turning the casing catcher for AR-style rifle **5** upside down and shaking the accumulated spent casings or cartridges out from the void above the magnetic weir plate **20**, through the same void in which the spent casings or cartridges were deposited into the cage **10**. In order to remove casing catcher for AR-style rifle **5** from the rifle **100**, the above installation procedure should be carried out in reverse order.

What is claimed is:

1. Casing catcher for AR-style rifle comprises: a cage; a magnetic weir plate; a lock pin receiver; a lock pin; a first key; and a second key, wherein,
 said cage comprises: an upper side, a lower side, a front side, a rear side, a left side, and a right side that are rigidly connected to form an enclosed container or cage with a gap or hole between said left side and said upper side,
 said magnetic weir plate is a rigid diagonal planar member with an upper surface, a lower surface, a front edge, a right edge, a rear edge, and a left edge,
 said magnetic weir plate is rigidly attached to said cage and located within said gap or hole between said left side and said upper side of said cage,
 said left edge of said magnetic weir plate further comprises at least one magnet rigidly attached thereto,
 said lock pin receiver is a rigid horizontal support member rigidly attached to said upper side of said cage,
 said lock pin receiver has a longitudinal axis,
 said lock pin receiver comprises a lock pin bore running parallel to said longitudinal axis of said lock pin receiver,
 said lock pin is rigid horizontal cylindrical member,
 said lock pin is removeably attachable within said lock pin bore,
 said lock pin receiver comprises at least one key slot,
 at least one key slot is a slot shaped void with a longitudinal axis that runs perpendicular to said longitudinal axis of said lock pin receiver,

said first key is an oblong rigid planar member with a right
facing foot protuberance and a lock pin hole,
said second key is an oblong rigid planar member with a
left facing foot protuberance and a lock pin hole,
said first and second keys are removeably attachable 5
within said at least one key slot,
said lock pin is removeably attachable within said lock
pin hole on said first key, and
said lock pin is removeably attachable within said lock
pin hole on said second key. 10

* * * * *